

# Marwood Manufactured Mortar Tray

## SAFETY INFORMATION / INSTRUCTION DETAILS

### 1. General.

This equipment is manufactured for use in the construction industry for the delivery or movement of mortar. **THE MAXIMUM PERMISSIBLE LOAD** marked on the equipment or the **SWL**, marked on the Test Certificate **MUST NOT BE EXCEEDED**.

The primary lifting equipment being utilised must conform to current European Machinery Regulations and have the correct **SAFE WORKING LOAD** certification for the radius being used. This equipment must only be operated by a trained and competent operator assisted by a qualified banksman.

Current Health and Safety legislation requires that all equipment used for lifting purposes must be issued with a Valid Test Certificate or a certificate of thorough examination.

### 2. Safety Instructions

**THE FOLLOWING INFORMATION IS ISSUED FOR YOUR SAFETY AND SHOULD BE OBSERVED AT ALL TIMES.**

- 2.1 This equipment should be subjected to a visual inspection prior to each use.
- 2.2 **ANY DAMAGE** sustained must be notified to a competent person immediately.
- 2.3 Should damage occur to the Lifting Eyes, Fork Pockets or any part of the main structure which effects the stability, **THE TEST CERTIFICATE WILL BECOME INVALID and YOU MUST STOP USING THE EQUIPMENT.**
- 2.4 When the equipment is being used with a forklift truck or similar, the forks must be fully engaged in the fork pockets provided.
- 2.5 All four fitted lifting eyes should be used when connecting to lifting a device. Failure to utilise all four lifting points will result in an unbalanced and unsafe load.
- 2.6 This Equipment should always be stored, lifted or landed to and from a firm level surface.
- 2.7 This equipment **MUST NOT** be used for transporting personnel.

### 3. Maintenance

- 3.1 Equipment should be subjected to a thorough examination by a competent person at six monthly intervals.
- 3.2 After use the equipment should be washed thoroughly to remove any residue using water and a stiff brush or pressure washer. Should it be necessary to chip off hardened concrete, you must wear eye protection.
- 3.3 It is recommended that all areas liable to contamination should be treated with a heavy duty mould oil or release agent before use.

Model	Description	Maximum Permissible Capacity	Maximum Permissible Load	Unladen Weight	Total Operational Weight
MT	Steel Mortar Tray	(Volume) 350ltrs	990 Kg	90 Kg	1080 Kg

**The equipment must not be modified or disassembled.**

MG399/07