

Marwood Group Ltd

MAN HOLE LIFTING PINS- TICK SHEET

| | | | | |
|---------------|-----------------------------|--|--|-------------|
| STATUS | Thorough Examination | | | DATE |
|---------------|-----------------------------|--|--|-------------|

| | | |
|----------------------|--|---------------------------|
| SERIAL NUMBER | | DESCRIPTION / TYPE |
|----------------------|--|---------------------------|

THESE INSTRUCTIONS SHOULD BE FOLLOWED WHEN CHECKING EQUIPMENT

- Ensure SWL is stamped on the pin lifting eye
- Examine pin body for any signs of distortion, twisting, cracking, corrosion, nicks or gouging. (The lifting pin must be straight)
- Examine Lifting eye for any signs of distortion, elongation or curling up of edges of lifting hole.
- Ensure quick release swivel plate is free moving and no signs of distortion, the pivot pin must be straight. Both arms must be parallel.

Equipment which displays evidence of incorrect operation should be withdrawn from service.

| | O K | R | COMMENTS |
|---------------------------|-----|---|----------|
| GENERAL APPEARANCE | | | |
| Main Body Condition | | | |
| Pin Body Condition | | | |
| SWL Marked | | | |
| Lifting Eye | | | |
| Quick release arm | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

Equipment should be cleaned and correctly stored after checking.

CHECKED BY

DATE:

| | |
|--------------|-------------|
| PRINT | SIGN |
|--------------|-------------|