

Brickfork/Block Grab Safety Nets - Check Sheet

STATUS	Final / On Hire		Off-Hire			Stock Transfer		Thorough Examination	Job sheet	DATE
PLANT DESCRIPTION / TYPE NUMBER										
Customer name										
Contract number										

THESE INSTRUCTIONS SHOULD BE FOLLOWED WHEN CHECKING THE NETS

- Make sure and record the serial number is legible on the tag. (Usually serial number is printed on green tag).
- Check the general appearance and condition of the whole safety net. Make sure that the safety net is free from excessive soiling, oil, concrete, paint and mud.
- Examine the metal bars and clamps, ensure clamps are secure and they are not cutting the rope.
- Check the border rope and all lifting loops. The rope should be threaded through the net and be spliced together secured with plastic tie-wraps. Examine for wear especially loop bearing points.
- Check the net for any signs of overloading, pulled stitching, cuts or fraying, especially
 areas that may be dragged or trapped should the net have been landed also check the
 corners.
- Check all areas of the net for any chemical contamination or melting of the net due to burns
- Always store nets inside in a clean, dry area and away from sunlight.

Equipment which displays evidence of incorrect operation should be withdrawn from service.

SCI VICC:	0.17	Т	COMMENTE
	ОК	R	COMMENTS
GENERAL APPEARANCE &			
CONDITION			
Label with Serial number			
(record)			
Metal bar & clamps ensure they			
do not cut rope.			
Condition of border rope, lifting			
loops & splicing.			
No evidence of cuts, fraying or			
overloading			
No chemical or heat damage			
Proper storage			
Entered on computer			The results of all off hire inspections must be
system			entered onto the computer system.

Equipment should be cleaned and correctly stored after checking

CHECKED BY:	DATE:
PRINT	SIGN